

Overview Accessories

Inflatable sewer pipe plugs



Type plug	75 - 150	100 - 200	150 - 300	200 - 400	300 - 600	400 - 800
max. pressure	2,5 bar	2,5 bar	2,5 bar	2,5 bar	2,5 bar	2,5 bar
Ø tube	Counterpressure in bar					
75	2					
80	1,9					
100	1,6	2				
110	1,5	1,9				
125	1,3	1,8				
150	0,8	1,3	2			
200		0,9	1,7	2		
225			1,5	1,9		
250			1,2	1,8		
275			1	1,6		
300			0,8	1,4	2	
350				1,1	1,8	
400				0,8	1,7	2
450					1,5	1,8
500					1,4	1,7
550					1,1	1,6
600					0,8	1,5
650						1,4
700						1,2
750						1
800						0,8

Legend :

Good

Consider an alternative

Other Ø preferable

Attention: unproper use of the sewer pipe plug can create life-threatening situations! The lessor cannot be held responsible for any damages on persons or goods, originated by wrongful use of the sewer pipe plug.



Type plug	75 - 150	100 - 200	150 - 300	200 - 400	300 - 600	400 - 800
Min. diameter (mm) :	75	100	150	200	300	400
Max. diameter (mm) :	150	200	300	400	600	800
Length (mm) :	350	350	470	550	710	1.150
Weight (kg) :	2	2,5	3,3	5,5	12	22

Material : natural rubber NNL45 reinforced with Kevlar/Aramide

Temperature range : -40°C till +80°C

Presentation : Sewer pipe plug + 10m hose with manometer, relief faucet and tire valve + 5m stainless steel chain